

# Genie SLA 20 - Material Lift

## Specifications

Model	SLA-20	
Measurements	US	Metric
Working height:		
standard forks - down	19 ft 6 in	5.94 m
standard forks - up	21 ft 2.5 in	6.46 m
<b>A</b> Height - stowed	6 ft 6.5 in	1.99 m
<b>B</b> Length - stowed	2 ft 5 in	.74 m
<b>C</b> Length - operating	6 ft 10 in	2.08 m
<b>D</b> Width - stowed	2 ft 7.5 in	.80 m
- with stabilizers lowered	6 ft 1 in	1.85 m
Width - straddle base		
minimum	----	----
maximum	----	----
maximum inside	----	----
<b>E</b> Ground clearance - center	2	.05 m
Load height minimum	6 in	.15 m

## Productivity

Load capacity:		
18 in (46 cm) load centre	800 lbs	363 kg
24 in (61cm) load centre	600 lbs	272 kg
42 in (107 cm) load centre	350 lbs	159 kg

## Power

Average cranks - per length unit		
standard winch - carriage moving	12.5 ft	41 m
standard winch - mast moving	5.5 ft	18 m

## Weight

Standard	405 lbs	184 kg
Straddle base	----	----

## Load Handling Attachments

Measurements	US	Metric
Standard	27/23.5/2.5 in	69/60/6 cm
Standard	2.5/1.5 in	6/4 cm
Weight	38.9 lbs	18 kg

## Standard Features

- Heavy-duty design
- Patented telescoping mast system
- Stabilizer set
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Maneuverable 4 in (10 cm) front casters and 5 in (13 cm) rear casters, with 4-way swivel locks and side brakes
- Compact design, legs fold up for easy storage
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport
- Winch locks load in place

