

Specifications

| Model | SLC-24 | |
|------------------------------------|-------------|--------|
| Measurements | US | Metric |
| Working height: | | |
| standard forks - down | 22 ft 3 in | 6.78 m |
| standard forks - up | 24 ft | 7.32 m |
| A Height - stowed | 7 ft 2 in | 2.18 m |
| B Length - stowed | 2 ft 10 in | .86 m |
| C Length - operating | 6 ft 9 in | 2.06 m |
| D Width - stowed | 2 ft 7.5 in | .80 m |
| - with stabilizers lowered | 5 ft 6 in | 1.68 m |
| Width - straddle base | | |
| minimum | ---- | ---- |
| maximum | ---- | ---- |
| maximum inside | ---- | ---- |
| E Ground clearance - center | 2 | .05 m |
| Load height minimum | 6 in | .15 m |

Productivity

| | | |
|----------------------------|---------|--------|
| Load capacity: | | |
| 14 in (36 cm) load centre | 650 lbs | 295 kg |
| 24 in (61cm) load centre | 425 lbs | 193 kg |
| 42 in (107 cm) load centre | 160 lbs | 73 kg |

Power

| | | |
|----------------------------------|--------|--------|
| Average cranks - per length unit | | |
| standard winch - | 8.5 ft | 27.8 m |

Weight

| | | |
|---------------|---------|--------|
| Standard | 347 lbs | 157 kg |
| Straddle base | ---- | ---- |

Load Handling Attachments

| Measurements | US | Metric |
|--------------|--------------|------------|
| Standard | 28/23/2.5 in | 71/58/6 cm |
| Weight | 26.5 lbs | 12 kg |

Standard Features

- Heavy-duty design
- Patented telescoping mast system
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Maneuverable 4 in (10 cm) front casters and 5 in (13 cm) rear casters, with 4-way swivel locks and side brakes
- Compact design, legs fold up for easy storage
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport
- Winch locks load in place
- Captive stabiliser set (standard on SLC 18 and 24)

