

Specifications

MODEL	GS™-1532	
MEASUREMENTS	Metric	US
Working height maximum	6.57 m	21 ft
A Platform height maximum	4.57 m	15 ft
B Platform length - outside	1.63 m	5 ft 4 in
- extended	2.54 m	8 ft 4 in
Slide-out platform extension deck	0.91 m	3 ft
C Platform width - outside	0.74 m	2 ft 5 in
Guardrail height:	1.10 m	3 ft 7 in
Toeboard height	0.15 m	6 in
D Height - stowed :fixed rails	1.96 m	6 ft 5 in
:folding guardrails	2.03 m	6 ft 8 in
:rails folded	1.73 m	5 ft 8 in
E Length	1.83 m	6 ft
Length	2.74 m	9 ft
F Width	0.81 m	2 ft 8 in
G Wheelbase	1.32 m	4 ft 4 in
H Ground clearance - centre	0.06 m	2.4 in
I - with pothole guards deployed	0.02 m	0.75 in

PRODUCTIVITY		
Maximum platform occupancy - indoor	2	2
Maximum platform occupancy - outdoor	1	1
Lift capacity	272 kg	600 lbs
Drive speed - stowed	4.0 km/h	2.5 mph
Drive speed - raised	0.8 km/h	0.5 mph
Gradeability	30%	30%
Turning radius - inside	zero	zero
Turning radius - outside	1.55 m	5 ft 1 in
Raise/lower speed	16 / 29 sec	16 / 29 sec
Controls	proportional	
Drive	dual front wheel	
Multiple disc brakes	dual rear wheel	
Tyres - solid non-marking	30 x 11 x 20 cm	12 x 4.5 x 8 in

POWER		
Power source	24 V (four 6 V 225 Ah batteries)	
Hydraulic system capacity	14.2 L	3.75 gal

WEIGHT		
	1,238 kg	2,729 lbs

STANDARDS COMPLIANCE CE EN280, PB-10-611-03, AS 1418.10

STANDARD FEATURES

PRODUCTIVITY

- Folding rails with half-height swing gate
- Dual front wheel drive
- Proportional lift and drive
- Platform control with battery charge indicator and diagnostic display
- Manual platform lowering valve
- Emergency stop at both platform and ground controls

- Rear wheel multiple disc brakes
- Front wheel hydraulic dynamic braking
- Manual brake release
- Pothole guards
- Tilt alarm
- Descent alarm
- Electronic horn
- Hour meter
- Dual flashing beacons
- Motion alarm

POWER

- 24 V DC (four 6 V 225 Ah batteries)
- Universal 20 amp smart charger

