

Specifications

| MODEL | GS™-1932 | |
|---|----------|------------|
| MEASUREMENTS | Metric | US |
| Working height maximum | 7.79 m | 25 ft |
| A Platform height maximum | 5.79 m | 19 ft |
| B Platform length - outside | 1.63 m | 5 ft 4 in |
| - extended | 2.54 m | 8 ft 4 in |
| Slide-out platform extension deck | 0.91 m | 3 ft |
| C Platform width - outside | 0.74 m | 2 ft 5 in |
| Guardrail height: | 1.10 m | 3 ft 7 in |
| Toeboard height | 0.15 m | 6 in |
| D Height - stowed :fixed rails | 2.00 m | 6 ft 7 in |
| :folding guardrails | 2.11 m | 6 ft 11 in |
| :rails folded | 1.75 m | 5 ft 9 in |
| E Length | 1.83 m | 6 ft |
| Length | 2.74 m | 9 ft |
| F Width | 0.81 m | 2 ft 8 in |
| G Wheelbase | 1.32 m | 4 ft 4 in |
| H Ground clearance - centre | 0.06 m | 2.4 in |
| I - with pothole guards deployed | 0.02 m | 0.75 in |

| PRODUCTIVITY | | |
|--------------------------------------|------------------|-----------------|
| Maximum platform occupancy - indoor | 2 | 2 |
| Maximum platform occupancy - outdoor | 1 | 1 |
| Lift capacity | 227 kg | 500 lbs |
| Drive speed - stowed | 4.0 km/h | 2.5 mph |
| Drive speed - raised | 0.8 km/h | 0.5 mph |
| Gradeability | 30% | 30% |
| Turning radius - inside | zero | zero |
| Turning radius - outside | 1.55 m | 5 ft 1 in |
| Raise/lower speed | 16 / 25 sec | 16 / 25 sec |
| Controls | proportional | |
| Drive | dual front wheel | |
| Multiple disc brakes | dual rear wheel | |
| Tyres - solid non-marking | 30 x 11 x 20 cm | 12 x 4.5 x 8 in |

| POWER | | |
|---------------------------|----------------------------------|----------|
| Power source | 24 V (four 6 V 225 Ah batteries) | |
| Hydraulic system capacity | 14.2 L | 3.75 gal |

| WEIGHT | | |
|--------|----------|-----------|
| | 1,500 kg | 3,307 lbs |

STANDARDS COMPLIANCE CE EN280, PB-10-611-03, AS 1418.10

STANDARD FEATURES

PRODUCTIVITY

- Folding rails with half-height swing gate
- Dual front wheel drive
- Proportional lift and drive
- Platform control with battery charge indicator and diagnostic display
- Manual platform lowering valve
- Emergency stop at both platform and ground controls

- Rear wheel multiple disc brakes
- Front wheel hydraulic dynamic braking
- Manual brake release
- Pothole guards
- Tilt alarm
- Descent alarm
- Electronic horn
- Hour meter
- Dual flashing beacons
- Motion alarm

POWER

- 24 V DC (four 6 V 225 Ah batteries)
- Universal 20 amp smart charger

