

Specifications

MODELS		GS™-3232	
MEASUREMENTS		Metric	US
Working height maximum		11.75 m	38 ft
A	Platform height maximum	9.75 m	32 ft
B	Platform height stowed	1.29 m	4 ft 2.75 in
C	Platform length - outside	2.26 m	7 ft 5 in
	- extended	3.18 m	10 ft 5 in
Slide-out platform extension deck		0.91 m	3 ft
D	Platform width - outside	0.81 m	2 ft 8 in
Guardrail height: fold down rails		1.10 m	3 ft 7 in
Toeboard height		0.15 m	6 in
E	Height (stowed) - folding rails	2.43 m	8 ft
	- rails folded	2.03 m	6 ft 8 in
F	Length - stowed	2.44 m	8 ft
G	Length - extended	3.33 m	10 ft 11 in
H	Width	0.81 m	2 ft 8 in
I	Wheelbase	1.85 m	6 ft 1 in
J	Ground clearance - centre	0.09 m	3.5 in
	- with pothole guards deployed	0.02 m	0.75 in

PRODUCTIVITY			
Maximum platform occupancy - indoor only		2	2
Lift capacity		227 kg	500 lbs
Extension deck capacity		113 kg	250 lbs
Drive height		6.71 m	22 ft
Drive speed - stowed		3.5 km/h	2.2 mph
Drive speed - raised		0.8 km/h	0.5 mph
Gradeability		25%	25%
Maximum outrigger levelling:			
	- front to back	3°	3°
	- side to side	5°	5°
Turning radius - inside		zero	zero
Turning radius - outside		2.13 m	7 ft
Raise / lower speed		57 / 40 sec	57 / 40 sec
Controls		proportional	
Drive		dual front wheel	
Multiple disc brakes		dual rear wheel	
Tyres - solid non-marking		38 x 13 x 28 cm	15 x 5 x 11 in

POWER			
Power source		24V DC (four 6V 225 Ah batteries)	
Hydraulic system capacity		14.2 L	3.75 gal

WEIGHT			
		2,352 kg	5,185 lbs

STANDARDS COMPLIANCE		ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10	
----------------------	--	---	--

STANDARD FEATURES

- Folding rails with half-height swing gate
- Automatic leveling outriggers
- Dual front wheel drive
- Proportional lift and drive
- Platform control with battery charge indicator and diagnostic display

- Onboard diagnostic system
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Multiple disc brakes
- Brake release
- Solid non-marking tyres
- Pothole guards

- Tilt alarm
- Descent alarm
- Electronic horn
- Dual flashing beacons
- Motion alarm

POWER

- 24V DC (four 6V 225 Ah batteries)
- Universal 20 amp smart charger

