

1932ES Electric Scissor Lift



SPECIFICATIONS

Performance:

Platform Height (max.)	5.80m
Working Height	7.80m
Lift Time	25 sec
Lower Time	26 sec
Platform Capacity Standard	230kg

Dimensions:

Stowed Height	2.10m
Minimum Transport Length	1.70m
Minimum Transport Height	2.10m
Overall Width	0.76m
Wheelbase	1.60m
Ground Clearance	0.09m
Platform Width	0.81m
Platform Length	1.70m
Standard Platform Extension	0.91m
Platform Height Lowered	1.00m
Maximum Drive Height	5.80m

Power:

Power Source	Battery
DC Voltage	24V
DC Power	220 Amp h
Hydraulic Pump Type	Gear
Batteries	4 x 6V
Charger	27 amp Universal Algorithm

Travel:

Tyre Size	323 x 100
Tyre Type	Solid/Non-marking
Inside Turning Radius	0m
Outside Turning Radius	1.69m
Drive Speed Elevated	0.8km/h
Gradeability with 2WD	25%
Indoor Rating Persons on Platform	2
Outdoor Rating 12.5m/sec Persons on Platform	1
Elevated Drive Time	22 hr

Weights and Capabilities:

Hydraulic Tank Capacity	7.00 Ltr
Operating Weight	1,565kg



STANDARD FEATURES

- 27 amp Multi-Function Universal Charger
- AC Receptacle in Platform
- Active Pothole Protection System
- All Motion Alarm
- Analyzer Port for Diagnostics
- Battery Condition Indicator
- Dynamic Braking
- Electric Drive
- Foot-Actuated Deck Extension
- Fork Lift Pockets
- Hourmeter

- Lanyard Attach Points
- Lifting and Tie Down Points
- Load Sensing System
- Lubrication Free Scissor Arm Bushings
- Manual Descent Cable
- Movable, Removable Platform Control
- QuikFold Rails
- Scissor Maintenance Prop
- Self-Closing Gate
- Steel Swing-Out Doors
- Tilt Alarm and Light
- Variable Tilt Visual Zone Indicator