

1932R6 Electric Scissor Lift



SPECIFICATIONS

Performance:

Platform Height (max.)	5.64m
Working Height	7.64m
Lift Time	25 sec
Lower Time	26 sec
Platform Capacity Standard	230kg

Dimensions:

Stowed Height	2.02m
Minimum Transport Length	2.07m
Minimum Transport Height	2.02m
Overall Width	0.81m
Wheelbase	1.39m
Ground Clearance	0.095m
Platform Width	0.75m
Platform Length	1.88m
Standard Platform Extension	0.70m
Platform Height Lowered	1.00m
Maximum Drive Height	5.64m

Power:

Power Source	Battery
DC Voltage	24V
DC Power	220 Amp h
Hydraulic Pump Type	Gear
Batteries	4 x 6V
Charger Electronic IP46 Input Voltage	190-250V AC

Travel:

Tyre Size	323 x 100
Tyre Type	Solid/Non-marking
Inside Turn Radius	0.6m
Outside Turn Radius	2.20m
Drive Speed Elevated	0.8km/h
Gradeability with 2WD	25%
Indoor Rating Persons on Platform	2
Outdoor Rating 12.5m/sec Persons on Platform	1
Elevated Drive Time	22 hr

Weights and Capabilities:

Hydraulic Tank Capacity	5.00Ltr
Operating Weight	1,588kg



STANDARD FEATURES

- 0 1932R6
- 0 1932R6
- 0 1932R6
- 7 202cm
- -
- V
- #
- k @
- † @
- @
- †
- h
- U
-) U 108