

4045R Electric Scissor Lift



SPECIFICATIONS

Performance:

Platform Height (max.) - Indoor	11.97m
Platform Height (max.) - Outdoor	8.80m
Working Height	13.97m
Working Height	10.80m
Lift Time	73 sec
Lower Time	48 sec
Platform Capacity Standard - Indoor	350kg
Platform Capacity Standard - Outdoor	250kg
Extension Platform Capacity	113kg

Dimensions:

Stowed Height - Rails Up	2.53m
Stowed Height - Rails Lowered	1.90m
Minimum Transport Length	2.71m
Overall Width	1.143m
Wheelbase	2.03m
Ground Clearance	0.127m
Platform Width	1.05m
Platform Length	2.43m
Standard Platform Extension	0.91m
Platform Height Lowered	1.40m
Maximum Drive Height - Indoor	Full Height
Maximum Drive Height - Outdoor	8.80m

Power:

Hydraulic Pump - Type	Fixed Displacement Gear
Batteries	4 x 12V

Travel:

Tyre Size	406 x 127mm
Tyre Type	Foam Filled/Non-marking
Inside Turn Radius	Zero
Outside Turn Radius	2.54m
Drive Speed Elevated	0.80km/h
Drive Speed Lowered	3.20km/h
Gradeability	25%

Weights and Capabilities:

Hydraulic Tank Capacity	30 Ltr
Operating Weight	3,175kg



STANDARD FEATURES

- Proportional Controls
- Battery Condition Indicator
- 110V-AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attach Points
- Movable, Removable Platform Control
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Scissor Maintenance Prop
- Self-centering arm stack
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- 36 in. (91 cm) Foot-Actuated Deck Extension
- Steel Swing-Out Doors
- Variable Tilt Visual Zone Indicator
- Manual Descent Cable
- Diamond Tread Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamic Braking
- Removable Ladder
- Complies with ANSI 92.20 Regulations