

S2632E SLAB SCISSOR LIFT

DIMENSIONS	S2632E
Max. working height	10.0m
Max. platform height (A)	8.0m
Platform size (stowed)	0.74m x 2.31m
Platform size (extended)	0.74m x 3.22m
Deck extension length (B)	0.91m
Overall width (C)	0.81m
Stowed length (D)	2.37m
Stowed height (E)	2.33m
Wheelbase	1.92m
Ground clearance (stowed)	63mm
Ground clearance (elevated)	19mm

PERFORMANCE	
Platform capacity (SWL)	227kg
Max. operating wind speed (1 person on platform)	0m/s
Max. drive height	8.0m
Max. drive speed (elevated)	0.6km/h
Max. drive speed (stowed)	3.2km/h
Raise/lower time	20/26sec
Gradeability	25%
Inside turning radius	0.25m
Outside turning radius	2.34m
Tyres	38.1cm x 12.7cm non-marking solid rubber
Controls	one-hand proportional joystick
Drive system	dual front wheel hydraulic motors

POWER	
Power source	24V 4hp DC electric motor 4 x 6V 240 Ah batteries

WEIGHT	
Gross weight	2,224kg

STANDARD FEATURES

- Proportional controls
- 0.9m extension deck
- Tilt alarm
- Swing-out service trays
- Power line to platform (no sockets)
- Horn
- Hour meter
- CE approved

TURNING RADIUS

