

20AM - 36AM Push Around Vertical Lifts



SPECIFICATIONS

Performance:	20AM	25AM	30AM	36AM
Platform Height (max.)	6.15m	7.60m	9.02m	11.00m
Working Height	8.15m	9.60m	11.02m	13.00m
Lift Time	45 sec	60 sec	75 sec	120 sec
Lower Time	35 sec	37 sec	39 sec	50 sec
Platform Capacity Standard	160kg		135kg	
Dimensions:				
Stowed Length	1.19m	1.24m	1.32m	1.38m
Stowed Height	1.19m	1.24m	1.32m	2.64m
Height tilted back				1.94m
Stabiliser Footprint Length	1.57m		1.89m	2.02m
Stabiliser Footprint Width	1.37m	1.35m	1.81m	2.00m
Platforms:				
Standard Platform Type	Steel Rail/Alloy Floor			
Overall Width	0.74m	0.74m	0.74m	0.74m
Standard Platform Size - W x L	0.66 x 0.66m			
Chassis Length	1.19m		1.38m	
Platform Entry Height	0.48m			
Power:				
Power Source	Battery			
DC Voltage	12V			
DC Power	93 Amp hr			
Weights and Capabilities:				
Operating Weight	390kg	410kg	427kg	526kg

STANDARD FEATURES

- Work in tight and confined vertical areas
- 4 easy fit outriggers with interlock switch and telltale light indicating each outrigger is locked and set
- Base can be levelled on outriggers
- Dual chain vertical mast lift
- Non-marking solid tyres
- 1 x 12V DC deep cycle battery
- Removable SCR automatic battery charger for quick recharging

