

10MSP Mobile Stock Picker



SPECIFICATIONS

Performance:

Platform Height (max.)	3.05m
Working Height	4.88m
Lift Time	13 sec
Lower Time	11 sec
Platform Capacity Standard	160kg
Parcel Tray Capacity	115kg

Dimensions:

Stowed Length	1.56m
Stowed Height	1.42m
Ground Clearance	0.05m

Platforms:

Standard Platform Type	Standard
Overall Length	1.52m
Overall Width	0.84m
Standard Platform Size - (WxL)	0.69 x 0.50m
Parcel Tray Size - (WxL)	0.66 x 0.66m
Platform Entry Height	0.33m

Power:

Power Source	Battery Sealed AGM
DC Voltage	24V
DC Power	200 Amp hr
Batteries	4 x 6V

Travel:

Tyre Type	Solid
Inside Turn Radius	0m
Drive Speed Elevated	1km/h
Gradeability	15%
Wind Rating	0m/sec

Weights and Capabilities:

GVW	500kg
-----	-------



STANDARD FEATURES

- Smooth control, proportional electric motor with reduction hub
- 2 wheel drive
- Proportional lift and lower
- Vertical dual chain mast lift
- Non-marking solid tyres
- 1.5 degree multi axis level sensor stops functions when elevated
- 4 x 6V DC deep cycle AGM batteries for spill free applications
- Electronic (inverter style) battery charger for quick recharges